



NEW

The Composite Drum Valve (CDV)

A Cost Effective & Safe Solution For Closed Liquid Transfer.

Elastomers
Standard in Viton & EPDM
with options in other
materials upon request.

DOT/UN
Certified

Reinforced Construction
Nylon container valve
body designed with cross
bars to maximize rigidity
and strength.

Secure-Ring
Ensures integrity of container
valve body assembly.

Tapered Spring
Centres the profile seal
for precise and consistent
closure of the container valve.
(Standard with AISI 302
Stainless Steel. Non-tapered
springs are available in AISI
316L SS and Hastelloy)

Flow Rate
Fill - 130 l/min
Dispense - 90 l/min
(water at ambient temperature)

CLOSED, SEALED & SECURE... For Purity, Performance & Protection.

CDV Closed Dispensing System

The Drum Valve (DV) / Reusable Stainless Valve (RSV) has become a standard for closed liquid transfer of chemicals from drums and IBCs.

Now the valve is also available in plastic, for products not compatible with stainless steel or where single trip logistics are in place. The plastic valve is compatible with all other components of the stainless steel system.

Features & Benefits

Cost Efficient and Safe

- Cost efficient for low value products
- Cost efficient for single use containers
- Enhanced user safety
- Improved product quality and integrity

Warranty

- 1 Year - CDV Container Valves (Cannot be rebuilt)
- 3 Years - DV/RSV Dispense Couplers

Quick & Easy to Use

- Uses the same couplers as the DV/RSV Closed System
- Connecting and disconnecting is simple



DV/RSV Fill Coupler

For use by Authorized Registrant Only
- Flow rate: 130 l/min
(water at ambient temperature)



DV/RSV Dispense Coupler

For use by End-User Operator
- Flow rate: 90 l/min
(water at ambient temperature)

**DV/RSV
Dust Cover**



**DV/RSV Tamper Evident
Shipping Cap**



**Tamper Evident
Crimp-On Ring**



DOT/UN Certified*

You can trust that when the CDV Closed System is transported by road in either a drum or IBC, the packaging remains Closed, Sealed & Secure.



CDV - Container Valve

Available threads:
- 56 x 4mm
- 2.5" x 5 buttress

Available seals:
- Viton
- EPDM

DV/RSV Down Tube

**DOT/UN
Certified**

*The RSV Container Valve has been DOT/UN tested & certified in a range of containers. Contact us for more details.

01262b-10713 Copyright © 2013 Micro Matic USA, Inc. All Rights Reserved.